

**Encon®**  
**SAFETY PRODUCTS**  
**1-800-283-6266**  
 phone: (713) 466-1449  
 email: customerservice@enconsafety.com

**EYE/FACEWASH  
 WITH YELLO-BOWL®  
 AND WALL BRACKET  
 PART NUMBER: 01035501**

**SPECIFICATION:**

Third party certified to ANSI Z358.1, the eye/facewash shall deliver 8.0 gpm (30.3 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Eye/Facewash shall provide a non-injurious stream of water for 15 minutes or longer. The eye/facewash shall be supplied with 1/2" chrome plated (CP) single motion activation stay open ball valve with CP ball. Eye/Facewash shall include SS actuator with actuation graphic, 7" X 11" (17.8 cm X 27.9 cm) sign, tailpiece and wall mounting bracket. Unit must be supplied with self-adjusting 8.0 gpm (30.3 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eye/Facewash heads with float off covers to be manufactured of UV resistant ABS plastic mounted in a high visibility ABS plastic Yello-Bowl®. Float off covers are secured with stainless steel bead chains and provided to inhibit dust and/or contamination when not in use. Eye/Facewash units that provide improper flow pattern or contain deteriorating screens/filters are not acceptable.

**Encon Safety Products Model 01035501** includes eye/facewash w/ Yello-Bowl® and wall bracket.

**Encon Safety Products Model 01035503** includes eye/facewash w/ Yello-Bowl® and wall bracket and strainer tee

**\*Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

**MATERIALS OF CONSTRUCTION:**

**PIPING:** 1/2" Chrome plated brass.

**VALVES:** 1/2" Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic. Strainer Tee Option: 1/2" BCP, 16 mesh

**HEAD:** ABS plastic dual stream heads with ABS plastic float off covers secured with stainless steel bead chains.

**BOWL:** High visibility ABS plastic Yello-Bowl® with wall mount bracket.

**REGULATOR:** Self-adjusting 8.0 gpm (30.3 lpm) regulator assures a constant and even dual stream flow pattern under varying hydraulic conditions.

**SUPPLY:** 1/2" NPT

**WASTE:** 1 1/4" x 6" (3.17cm X 15.24 cm) long slip joint tailpiece.

**WEIGHT:** 6 lbs (2.72 kgs)

